

Water Based Silicone Rubber Release Agent for Conveyor Belt Air spring demolding

Our Product Introduction

for more products please visit us on shlorechem.com

Basic Information

- Place of Origin: China
- Brand Name: Lubekote
- Model Number: xxxxx
- Minimum Order Quantity: None
- Price: 1-99 usd
- Packaging Details: 25L, 200L
- Delivery Time: 5-15 working days
- Payment Terms: T/T
- Supply Ability: 20T/week



Product Specification

- Product Name: Water Based Mold Release Agent
- Classification: Chemical
- Name: Mold Release Agent For Air Spring
- Odor: Slight
- Application: Air Spring Demolding
- Diluent: Water
- Feature: Environmental Friendly
- Advantages: No Build Up
- Highlight: **Conveyor Belt Silicone Mould Release Agent, Air Spring Demolding Release Agents, Water Based Release Agent For Silicone Molds**

Product Description

Water Based Mold Release Agent for Conveyor Belt Rubber Demolding No Build Up

Air spring release agent is a spring form made of the elastic force generated by air compression, which is mainly used in the shock absorber system of various vehicles. In the production process of air spring release agent, surface problems are more common, and the treatment methods are not the same.

One of the problems is the capsule crack, which generally appears near the surface of the submouth, such as uneven brushing of the release agent or local leakage, resulting in serious bonding of the capsule after vulcanization, and cracks caused by local tearing of the capsule when the mold is opened, resulting in product scrap.

Lorechem water release agent is suitable for rubber air spring capsule, its main function is to make the release operation easy, to prevent the damage caused by forced removal of the product.

Water Based Mold Release Agent for air spring Advantages:

Easy to use

Eco friendly

Easy demoulding, less mold residue

Dry film without oil, tape surface wireless marks

Excellent release properties

Not affect subsequent sand blasting and other post processes

Water Based Mold Release Agent for air spring Application:

Molds should be clean before using.

Apply a thin coat of our release agent.

Wait until the water is evaporated.

Start production

Handling precautions:

For industrial use only.

Prolonged skin contact with high concentrate dilutions should be avoided. Accidental splashes in the eye should be washed out with copious amounts of water.

Do not allow product to freeze.

More release agent for Rubber Industry:

Application	Suitable code	Dispersing medium	Advantages
Antivibration	Lubekote 9421A/9140	Water based	Environmentally friendly; Can be diluted multiple times; It has strong durability and good releasing effect; Excellent performance of surface gloss; Cost-effective; Prolongs the mold cleaning cycle.
Antivibration	Lubekote 9526	Solvent based	It has strong durability and good releasing effect; Excellent performance of surface gloss; Economical dosage; Prolongs the mold cleaning cycle. Excellent performance of surface gloss; Cost-effective; Good performance on post process; Prolongs the mold cleaning cycle applied as both semi-permanent and highly diluted.
Antivibration	Lubekote 9425	Solvent based	It has strong durability and good releasing effect; Less build-up on molds; Cost-effective; Good performance on post process.
Hose	Lubekote 9240	Water based	Environmentally friendly; Excellent anti-tack agent for rollers, drums and autoclave vulcanisation operations
Hose	Lubekote 9808	Solvent based	Non greasy, non contaminating coating; Good releasing effect; Excellent performance of produced parts.
Belt	Lubekote 9836A	Water based	Environmentally friendly; Good releasing effect.
Belt	Lubekote 9328	Solvent based	Fast drying; Good releasing effect; Cost-effective.
Tire	Lubekote 9919	Water based	Semi-permanent lubricant system designed for coating of Bladders and touch up coats on Bladders or Green Tires; Easy to apply; Provides true multiple releases; Universal for all tires.
Tire	Lubekote 9502A/9503A	Water based	Semi-permanent water-based release agent applied on tire molds. The gloss level of part surface gloss is adjustable.
Silicone & Fluorine rubber	Lubekote 9165C	Water based	Applied for releasing hard-to-release rubber such as fluorine rubber ; Can be used as both semi-permanent and highly diluted. As semi-permanent it has strong durability and good releasing effect; Excellent performance of surface gloss; Cost-effective; Good performance on post process;





Shanghai Lorechem Co., Ltd. was established in 2008. It is a high-tech enterprise which is dedicated to serve releasing products which involve semi-permanent release agent, anti-sticking, surface lubrication and thermal reactive adhesive.



Shanghai Lorechem Company Limited



export@lorechem.com



shlorechem.com

Floor 2-3, Building 20, Hongxing International Plaza, Lane 1818, Lianhang Road, Pujiang, Shanghai