

Clear Liquid PU Mold Release Agent for CPU Wheel Solvent Base Concentrate

Our Product Introduction

for more products please visit us on shlorechem.com

Basic Information

- Place of Origin: China
- Brand Name: Lubekote
- Model Number: 9129
- Minimum Order Quantity: None
- Price: Negotiated
- Packaging Details: 25L, 200L
- Delivery Time: 5-15 working days
- Payment Terms: T/T
- Supply Ability: 20T/week



Product Specification

- Type: Solvent Base Concentrate
- Application: Mold Release Agent For CPU Wheels
- Product Code: Lubekote 9129
- Package: 20L/200L
- Appearance: Clear Liquid
- Highlight: **CPU Wheel PU Mold Release Agent,
Solvent Base PU Mold Release Agent,
Liquid PU Mold Release Agent**

Product Description

Clear Liquid PU Mold Release Agent for Industry Applications Solvent Base Concentrate

Product Description:

Our Mold Release Agent LubeKote 9129 is uniquely tailored for use with CPU (Cast Polyurethane) wheel molds, offering excellent compatibility and reliable results. Its clear liquid formulation allows for easy application and ensures minimal interference with the visual appearance of the finished CPU wheels.

Features:

Product Name: PU Mold Release Agent

Product Line: LubeKote 9129

Density: 0,96-1,00 G/cm³

Shelf Life: 24 Months

Type: Solvent Base Concentrate

Application: CPU wheel demolding

Technical Parameters:

Appearance	Clear liquid
Shelf life	24 months
Density	0,96-1,00 g/cm ³

Applications:

Dilution and Mixing:

Prepare a suitable dilution of the product by adding a solvent, such as naphtha or heptane, to achieve the desired solid content.
2. The recommended dilution ratio is typically 10-30 parts of solvent to the product, ensuring optimal performance.

Mold Surface Preparation:

Prior to application, ensure the mold surface is meticulously cleaned and free from any debris or residue.

Application:

Apply a minimum of two thin and even coats of the release agent onto the mold surface, ensuring uniform coverage.

It is best to apply the coats at the process temperature for optimal results.

Allow a brief drying time to ensure proper adhesion and effectiveness.

Maintenance:

To maintain the desired level of release and lubrication, reapply a light coat of the release agent at the process temperature when necessary.

Additional Application Variations:

For enhanced results, consider adjusting the number of coats applied based on the specific requirements of your CPU wheel manufacturing process.

Achieve the desired release and lubrication by applying multiple thin coats rather than just two coats.

Optimal Performance:

To optimize the performance of the release agent, ensure that the coats applied are uniform and evenly spread across the mold surface.

Packing and Shipping:

Package size: 20L , 200L

Shipping: By sea, By air





Warehousing and logistics



It has nearly 5,000 square meters of cargo storage area. Eight employees work full-time in warehousing.



Technical support



Making adjustment in the field



Shanghai Lorechem has a professional technical service team, whose members are specialized in polymer materials engineering. They have a wealth of field testing.

Testing in the field



Shanghai LoreChem Co., Ltd. was established in 2008. It is a high-tech enterprise which is dedicated to serve releasing products which involve semi-permanent release agent, anti-sticking, surface lubrication and thermal reactive adhesive. Shanghai LoreChem has been improving product quality for 15 years. The releasing products are mainly applied in rubber, polyurethane and composite industry. The brand of Lubekote for release agent and Thinkbond for adhesive have been registered in China. Both of them are well known in the industry.

Shanghai LoreChem's business is all over the domestic and foreign high-end production enterprises by providing professional technical solutions and services. The company's long-term goal is to become one of the best suppliers of release agent in Asia.



Shanghai Lorechem Company Limited



export@lorechem.com



shlorechem.com

Floor 2-3, Building 20, Hongxing International Plaza, Lane 1818, Lianhang Road, Pujiang, Shanghai