

PU Mold Release Agent Solvent Base Concentrate for CPU Wheels

Our Product Introduction

for more products please visit us on shlorechem.com

Basic Information

- Place of Origin: China
- Brand Name: Lubekote
- Model Number: 9129
- Minimum Order Quantity: None
- Price: Negotiated
- Packaging Details: 25L, 200L
- Delivery Time: 5-15 working days
- Payment Terms: T/T
- Supply Ability: 20T/week



Product Specification

- Type: Solvent Base Concentrate
- Application: Mold Release Agent For CPU Wheels
- Product Code: Lubekote 9129
- Package: 20L/200L
- Appearance: Clear Liquid
- Highlight: **CPU Wheel PU Mold Release Agent,
Solvent Base PU Mold Release Agent,
Liquid PU Mold Release Agent**



Product Description

Lubekote 9129 - PU Mold Release Agent

Solvent Base Concentrate for CPU Wheel Molds

Product Specifications

Type	Solvent Base Concentrate
Application	Mold Release Agent for CPU wheels
Product Code	Lubekote 9129
Package	20L/200L
Appearance	Clear liquid

Product Description

Our Mold Release Agent LubeKote 9129 is specifically formulated for CPU (Cast Polyurethane) wheel molds, providing excellent compatibility and reliable performance. The clear liquid formulation ensures easy application without affecting the visual quality of finished CPU wheels.

Key Features

Product Name: PU Mold Release Agent

Product Line: Lubekote 9129

Density: 0.96-1.00 G/cm³

Shelf Life: 24 Months

Type: Solvent Base Concentrate

Application: CPU wheel demolding

Technical Parameters

Appearance	Clear liquid
Shelf life	24 months
Density	0.96-1.00 g/cm ³

Application Instructions

Dilution and Mixing

Dilute with solvent (naphtha or heptane) to achieve desired solid content

Recommended dilution ratio: 10-30 parts solvent to product

Mold Surface Preparation

Ensure mold surface is thoroughly cleaned and free from debris before application.

Application Process

Apply minimum two thin, even coats for uniform coverage

Apply at process temperature for optimal results

Allow brief drying time between coats

Maintenance

Reapply light coat at process temperature when needed to maintain release performance.

Performance Optimization

Adjust number of coats based on specific process requirements

Multiple thin coats preferred over fewer thick coats

Ensure uniform, even application across mold surface

Packaging & Shipping

Package sizes: 20L, 200L

Shipping methods: By sea, By air

Product Images








Warehousing and logistics



It has nearly 5,000 square meters of cargo storage area. Eight employees work full-time in warehousing.







Technical support



Making adjustment in the field



Shanghai Lorechem has a professional technical service team, whose members are specialized in polymer materials engineering. They have a wealth of field testing.

Testing in the field



About Shanghai LoreChem Co., Ltd.

Established in 2008, Shanghai LoreChem is a high-tech enterprise specializing in release products including semi-permanent release agents, anti-sticking solutions, surface lubrication, and thermal reactive adhesives. With 15 years of continuous quality improvement, our products serve the rubber, polyurethane, and composite industries.

Our brands Lubekote (release agents) and Thinkbond (adhesives) are well-known in the industry. We provide professional technical

solutions to domestic and international high-end manufacturers, with the long-term goal of becoming one of Asia's premier release agent suppliers.



Shanghai Lorechem Company Limited



15901891635



export@lorechem.com



shlorechem.com

Floor 2-3, Building 20, Hongxing International Plaza, Lane 1818, Lianhang Road, Pujiang, Shanghai