China

T/T

Chemical

Lubekote

Slight

Lubekote

Solvent Based Rubber Mold Release Agent Translucent Liquid For Injection Molding

Basic Information

- Place of Origin:
- Brand Name:
- Model Number: XXXXX • Minimum Order Quantity: None
- Price:
- 1-99 usd 25L, 200L • Packaging Details:
- Delivery Time: 5-15 working days
- Payment Terms:
- Supply Ability: 20T/week



Product Specification

- Classification:
- Name:
- Brand Name:
- Odor:
- Place Of Origin:
- Diluter:
- Highlight:

China Solvent Injection Molding Rubber Mold Release Agent, OEM Solvent Based Mold Release Agents, Translucent Liquid Solvent Based Release Agent

Rubber Mold Release Agent

Our Product Introduction

Solvent Based Rubber Mold Release Agent Lubekote TS-55-013

TS-55-013 is formulated as a specialized solvent-based release agent which is a solid activation agent dispersion. It provides a dry and colorless coating with low friction and excellent mold releasing and antitack properties. Most commonly used in rubber and plastic materials. It can provide multiple cycles without transfer to the products parts and minimal building-up on mold. TS-55-013 can also be applied in thermosetting resin (epoxy, polyurethane and unsaturated resin)

Properties:

Colour: Translucent liquid

Shelf life: 24 months minimum

The polymeric resin used in TS-55-013 reacts with moisture. Please ensure can is resealed after use. TS-55-013 is supplied ready to use, no shaking or mixing is required. Do not mix with other products or solvents.

Advantages:

Suitable for all kinds of rubber and plastic compounds.

Clean, colorless, oil-free.

Does not contain oil, fat, stearic acid, wax and silicon compounds.

Does not transfer to the product parts.

Smooth the mold surface and protect the mold.

No bad effect on the subsequent molding process.

Semi-permanent release agent, provide multiple cycles.

Excellent chemical and thermal stability.

Improve production efficiency, reduce defective rate.

Application:

Thoroughly clean the surface. Apply at least two uniform, thin coats at process temperature. Allow a short drying time. Reapply a light coat at process temperature when required to maintain desired release and lubrication.

Handling precautions:

For industrial use only.

More release agent for Rubber Industry:

Application	Suitable code	Dispersing medium	Advantages
Antivibration	Lubekote 9421A/ 9140	Water based	Environmentally friendly; Can be diluted multiple times; It has strong durability and good releasing effect; Excellent performance of surface gloss; Cost-effective; Prolongs the mold cleaning cycle.
Antivibration	Lubekote 9526	Solvent based	It has strong durability and good releasing effect; Excellent performance of surface gloss; Economical dosage; Prolongs the mold cleaning cycle.Excellent performance of surface gloss; Cost-effective; Good performance on post process; Prolongs the mold cleaning cycle applied as both semi-permanent and highly diluted.
Antivibration	Lubekote 9425	Solvent based	It has strong durability and good releasing effect; Less build-up on molds; Cost-effective; Good performance on post process.
Hose	Lubekote 9240	Water based	Environmentally friendly; Excellent anti-tack agent for rollers, drums and autoclave vulcanisation operations
Hose	Lubekote 9808	Solvent based	Non greasy, non contaminating coating; Good releasing effect; Excellent performance of produced parts.
Belt	Lubekote 9836A	Water based	Environmentally friendly; Good releasing effect.
Belt	Lubekote 9328	Solvent based	Fast drying; Good releasing effect; Cost-effective.
Tire	Lubekote 9919	Water based	Semi-permanent lubricant system designed for coating of Bladders and touch up coats on Bladders or Green Tires; Easy to apply; Provides true multiple releases; Universal for all tires.
Tire	Lubekote 9502A/9503A	Water based	Semi-permanent water-based release agent applied on tire molds. The gloss level of part surface gloss is adjustable.
Silicone & Fluorine rubber	Lubekote 9165C	Water based	Applied for releasing hard-to-release rubber such as fluorine rubber ; Can be used as both semi-permanent and highly diluted. As semi-permanent it has strong durability and good releasing effect; Excellent performance of surface gloss; Cost-effective; Good performance on post process;





















