

Anti Stick Spacer Mold Release Agent, Mould Release Agent For Rubber

Basic Information

Place of Origin: China
Brand Name: Lubekote
Model Number: xxxxx
Minimum Order Quantity: None
Price: 1-99 usd
Packaging Details: 25L, 200L

• Delivery Time: 5-15 working days

Payment Terms: T/TSupply Ability: 20T/week



Product Specification

Product Name: Anti-stick Spacer

Classification: ChemicalOdor: Slight

• Application: Rubber Parts Anti-stick

• Highlight: Anti Stick Spacer Rubber Mould Release Agent,

Rubber Spacer Mould Release Agent, Lubekote Rubber Release Agents

Product Description

Lubekote Anti-stick Spacer for Rubber Products

Rubber spacer is a film spacer in rubber processing, is a class of operational additives, LubeKote anti-stick Spacer aqueous solution can form a thin layer of isolation film on the surface of the rubber material, its main role is to prevent the film or semi-finished surface of the mutual bonding. It is often used in plasticizing, mixing, pressing and forming of raw rubber and rubber materials to prevent the adhesion of unvulcanized film and mixed film during parking.

It is suitable for the common anti-stick isolation process for all kinds of raw rubber and synthetic rubber and the release process for high-pressure hose extrusion.

Advantages:

It is suitable for all rubber products, because it can give the rubber surface good smoothness, so in each process can effectively prevent the adhesion between the rubber.

It is diluted with water and then used. Compared with traditional powder isolators, it will not cause working environment pollution and human health problems caused by uneven application of raw rubber surface or powder flying everywhere;

This product will not affect the bonding between rubber layers after vulcanization, and achieve thorough bonding between rubber layers, will not affect the physical properties of vulcanized products.

The processed product has a beautiful and smooth surface, no slip phenomenon, and a clean operating environment on site;

Rubber products will not bring pollution traces and other problems, so it is a new type of environmental protection products, harmless to the human body, non-corrosive.

If used as a stripping agent, the stripping effect is excellent, and the surface of the product after vulcanization is smooth and clean as new.

Handling precautions:

For industrial use only.

Prolonged skin contact with high concentrate dilutions should be avoided. Accidental splashes in the eye should be washed out with copious amounts of water.

Do not allow product to freeze.

More release agent for Rubber Industry:

Application	Suitable code	Dispersing medium	Advantages
Antivibration	Lubekote 9421A/ 9140	Water based	Environmentally friendly; Can be diluted multiple times; It has strong durability and good releasing effect; Excellent performance of surface gloss; Cost-effective; Prolongs the mold cleaning cycle.
Antivibration	Lubekote 9526	Solvent based	It has strong durability and good releasing effect; Excellent performance of surface gloss; Economical dosage; Prolongs the mold cleaning cycle.Excellent performance of surface gloss; Cost-effective; Good performance on post process; Prolongs the mold cleaning cycle applied as both semi-permanent and highly diluted.
Antivibration	Lubekote 9425	Solvent based	It has strong durability and good releasing effect; Less build-up on molds; Cost-effective; Good performance on post process.
Hose	Lubekote 9240	Water based	Environmentally friendly; Excellent anti-tack agent for rollers, drums and autoclave vulcanisation operations
Hose	Lubekote 9808	Solvent based	Non greasy, non contaminating coating; Good releasing effect; Excellent performance of produced parts.
Belt	Lubekote 9836A	Water based	Environmentally friendly; Good releasing effect.
Belt	Lubekote 9328	Solvent based	Fast drying; Good releasing effect; Cost-effective.
Tire	Lubekote 9919	Water based	Semi-permanent lubricant system designed for coating of Bladders and touch up coats on Bladders or Green Tires; Easy to apply; Provides true multiple releases; Universal for all tires.
Tire	Lubekote 9502A/9503A	Water based	Semi-permanent water-based release agent applied on tire molds. The gloss level of part surface gloss is adjustable.
Silicone & Fluorine rubber	Lubekote 9165C	Water based	Applied for releasing hard-to-release rubber such as fluorine rubber; Can be used as both semi-permanent and highly diluted. As semi-permanent it has strong durability and good releasing effect; Excellent performance of surface gloss; Cost-effective; Good performance on post process;

























Shanghai Lorechem Co., Ltd. was established in 2008. It is a high-tech enterprise which is dedicated to serve releasing products which involve semi-permanent release agent, anti-sticking, surface lubrication and thermal reactive adhesive.







shlorechem.com

Floor 2-3, Building 20, Hongxing International Plaza, Lane 1818, Lianhang Road, Pujiang, Shanghai