

China

Lubekote

# Permanent Water Based Mold Release For Seals Abrasion Resistance

# **Basic Information**

- Place of Origin:
- Brand Name:
- Model Number: XXXXX None
- Minimum Order Quantity:
- Price: 1-99 usd 25L, 200L
- Packaging Details:
- Delivery Time: 5-15 working days T/T
- Payment Terms:
- Supply Ability: 20T/week



## **Product Specification**

	Seals water based mold release, Abrasion Resistance mold release chemicals	
Highlight:	Permanent water based mold release,	
<ul> <li>Advantage:</li> </ul>	Permanent	
<ul> <li>Diluent:</li> </ul>	Water	
<ul> <li>Application:</li> </ul>	Seals Demoulding	
<ul> <li>Place Of Origin:</li> </ul>	China	
• Odor:	Slight	
<ul> <li>Brand Name:</li> </ul>	Lubekote	
• Name:	Mold Release Agent	
<ul> <li>Classification:</li> </ul>	Chemical	

Our Product Introduction

#### Permanent Water Based Release Agent for Seals

#### **Application Field:**

It is a permanent water-based release system and protection coating designed for molding and coating operations. Rubber, all kind of rubber-types, Tires, Thermoplastic, Thermoset resins, Polyurethane, Wood Composite, EVA, Various Surfaces (Articles like Saws, Pans, Bakery Plates etc.)

#### Advantages:

non-transfer of release agent high temperature stability high degree of slip abrasion resistance of the release film Excellent performance of produced parts Provides true multiple releases between application **Application:** 

### The mold should be thoroughly cleaned.

Mold cleaning and release agent application should be performed in a well ventilated area.

Apply a thin coat at process temperature. It is recommended to apply at least two coats at the beginning.

After a short drying time it is ready to make production.

Reapply a light coat when necessary.

### Handling precautions:

For industrial use only.

Prolonged skin contact with high concentrate dilutions should be avoided. Accidental splashes in the eye should be washed out with copious amounts of water.

Application	Suitable code	Dispersing medium	Advantages
Antivibration	Lubekote 9421A/ 9140	Water based	Environmentally friendly; Can be diluted multiple times; It has strong durability and good releasing effect; Excellent performance of surface gloss; Cost- effective; Prolongs the mold cleaning cycle.
Seals & Gaskets	Lubekote 9165C	Water based	Can be used as both semi-permanent and highly diluted. Applied as semi- permanent it has strong durability and good releasing effect; Excellent performance of surface gloss; Cost- effective;
Hose	Lubekote 9240	Water based	Environmentally friendly; Excellent anti- tack agent for rollers, drums and autoclave vulcanisation operations
Belt	Lubekote 9836A	Water based	Environmentally friendly; Good releasing effect.
Tire	Lubekote 9919	Water based	Semi-permanent lubricant system designed for coating of Bladders and touch up coats on Bladders or Green Tires; Easy to apply; Provides true multiple releases; Universal for all tires.
Tire	Lubekote 9502A/9503A	Water based	Semi-permanent water-based release agent applied on tire molds. The gloss level of part surface gloss is adjustable.
Silicone & Fluorine rubber	Lubekote 9165C	Water based	Applied for releasing hard-to-release rubber such as fluorine rubber ; Can be used as both semi-permanent and highly diluted. As semi-permanent it has strong durability and good releasing effect; Excellent performance of surface gloss; Cost-effective; Good performance on post process;
Silicone & Fluorine rubber	Lubekote 9440A	Water based	Applied to release silicone and EPDM; Designed for molding operations when non-transfer of release agent, high temperature stability, high degree of slip, and abrasion resistance of the release film are important.
CPU	Lubekote 9120A	Water based	Environmentally friendly; Easy to apply; Prolongs the mold cleaning cycle.

for more products please visit us on shlorechem.com

Flexible foam	Lubekote 9820A	Water based	Environmentally friendly; Low VOC; Delicate skin, highly diluted; Less contaminating mold.
ISF	Lubekote 9810G	Water based	5~10 times dilution; Cost-effective; Less contaminating mold; strong demolding; Universal for all ISF.
Encapsulatic n	Lubekote 9808E	Water based	Matt finish; Excellent performance of produced parts; Less contaminating mold; strong demolding; Universal for all encapsulation.



Warehousing and logistics

It has nearly 5,000 square meters of cargo storage area. Eight employees work full-time in warehousing.







