

Resin Solvent Based Concrete Release Agent Slight Odor

Our Product Introduction

for more products please visit us on shlorechem.com

Basic Information

- Place of Origin: China
- Brand Name: Lubekote
- Model Number: xxxxx
- Minimum Order Quantity: None
- Price: 1-99 usd
- Packaging Details: 25L, 200L
- Delivery Time: 5-15 working days
- Payment Terms: T/T
- Supply Ability: 20T/week



Product Specification

- Classification: Chemical
- Name: Mold Release Agent
- Brand Name: Lubekote
- Odor: Slight
- Place Of Origin: China
- Application: Demolding For Resin Concrete
- Diluent: Solvent
- Highlight: **Solvent Based Concrete Release Agent ,
Resin Concrete Release Agent ,
Slight Odor mold release agent**

Product Description

Mold Release Agent for Resin Concrete Solvent Based Multiple Releases

Application Field:

It is a lubricant and release system designed for resin concrete industry.
It has shown excellent performance in releasing resin concrete parts.
It can be diluted with solvent.

Advantages:

Does not transfer to the product parts.
Low odour
No knit lines.
Minimal build-up on mold
Excellent surface

Application:

The mold should be thoroughly cleaned.

Mold cleaning and release agent application should be performed in a well ventilated area.

1. Apply Lubekote release agent to clean, dry cotton cloth.
 2. Gently wipe over mold surface covering an area of approximately 0,5 m². Vigorous rubbing or polishing is not required.
 3. Repeat steps 1 and 2 on the adjacent area. Ensure a good overlap with the previous area to provide complete coverage
 4. Repeat until mold is completely coated.
 5. When dry, allow a further 15 minutes between coats for the film to cure.
 6. Repeat Steps 1- 5 above for a further 3 coats (4 in total).
 7. When dry, allow final film to cure for at least 30 minutes at room temperature before molding. Allowing a longer cure or heat curing (e.g. 15 min. at 60 °C) will improve film durability
- Reapply one coat of Lubekote release agent in the same way as described above when release becomes hesitant.

Handling precautions:

For industrial use only.

Application	Product	Advantages
Electrolytic cell	Lubekote 9023/9072/9043	Environmental protection and high performance, multiple demoulding, mold cleaning, secondary process
Gutter/drain pipe	Lubekote 9036L/9510/9289M	high cost performance, smooth demoulding, environmental protection without stimulation, protect the mold





Shanghai Lorechem Company Limited



export@lorechem.com



shlorechem.com

Floor 2-3, Building 20, Hongxing International Plaza, Lane 1818, Lianhang Road, Pujiang, Shanghai