Shanghai Lorechem Company Limited shlorechem.com

High Dilution Semi Permanent Mold Release Agent Water Based For Rubber Anti Vibration Parts

Basic Information

Place of Origin: China
Brand Name: Lubekote
Model Number: xxxxx
Minimum Order Quantity: None
Price: 1-99 usd
Packaging Details: 25L, 200L

• Delivery Time: 10-15 working days

• Payment Terms: T/T

• Supply Ability: 20T/month



Product Specification

Classification: Chemical

Name: Mold Release Agent

Brand Name: Lubekote
Appearance: Liquid
Odor: Slight
Place Of Origin: China

Application: Antivibaration Part

Diluent: Deionized Or Distilled Water

Highlight: High Dilution Semi Permanent Mold Release

Agent

Semi Permanent Mold Release Agent Water

Based

, Liquid high temperature mold release $% \left(1\right) =\left(1\right) \left(1\right)$



Product Description

Semi-Permanent Release Agent for Rubber Antivibaration Parts High Dilution Water Based

Properties: State: liquid

Density: 0.97-1.03 g/cm³ Shelf life: 12 months **Application Field:**

A is a release system designed for molding operations. It produces a durable film on the mold surface capable of providing many releases before reapplication is necessary. It will not contaminate the released surface. It is ready to use. But it can be diluted in some cases.

Advantages:

Water based, no VOC
Easy to apply
Multiple releases per application
Excellent slip and air bleed
Excellent performance of produced tires
Thin layers give best results and cost-effective
Universal for all tires

Application:

Molds should be clean before using. Apply a thin coat of our release agent. Wait until the water is evaporated. Start production

Handling precautions:

For industrial use only.

Prolonged skin contact with high concentrate dilutions should be avoided. Accidental splashes in the eye should be washed out with copious amounts of water.

Do not allow product to freeze.

More Semi-permanent release agent:

Application	Suitable code	Dispersing medium	Advantages
Seals & Gaskets	Lubekote 9165C	Water based	Can be used as both semi-permanent and highly diluted. Applied as semi-permanent it has strong durability and good releasing effect; Excellent performance of surface gloss; Cost-effective;
Tire	Lubekote 9919	Water based	Semi-permanent lubricant system designed for coating of Bladders and touch up coats on Bladders or Green Tires; Easy to apply; Provides true multiple releases; Universal for all tires.
Tire	Lubekote 9502A/9503A	Water based	Semi-permanent water-based release agent applied on tire molds. The gloss level of part surface gloss is adjustable.
Silicone & Fluorine rubber	Lubekote 9165C	Water based	Applied for releasing hard-to-release rubber such as fluorine rubber; Can be used as both semi-permanent and highly diluted. As semi-permanent it has strong durability and good releasing effect; Excellent performance of surface gloss; Cost-effective; Good performance on post process;









Technical support



Shanghai Lorechem has a professional technical service team, whose members are specialized in polymer materials engineering. They have a wealth of field testing.



oreChem

Shanghai LoreChem Co., Ltd. was established in 2008. It is a high-tech enterprise which is dedicated to serve releasing products which involve semi-permanent release agent, anti-sticking, surface lubrication and thermal reactive adhesive. Shanghai LoreChem has been improving product quality for 15 years. The releasing products are mainly applied in rubber, polyurethane and composite industry. The brand of Lubekote for release agent and Thinkbond for adhesive have been registered in China. Both of them are well known in the industry.

Shanghai LoreChem 's business is all over the domestic and foreign high-end production enterprises by providing professional technical solutions and services. The company's long-term goal is to become one of the best suppliers of release agent in Asia.

15901891635

export@lorechem.com



shlorechem.com

Floor 2-3, Building 20, Hongxing International Plaza, Lane 1818, Lianhang Road, Pujiang, Shanghai