Hihg Performance Water Based Release Agent For Belts

Basic Information

Place of Origin: China
Brand Name: Lubekote
Model Number: xxxxx
Minimum Order Quantity: None
Price: 1-99 usd
Packaging Details: 25L, 200L

• Delivery Time: 5-15 working days

Payment Terms: T/TSupply Ability: 20T/week



Product Specification

Product Name: Water Based Mold Release Agent

Classification: Chemical

Name: Mold Release Agent For Belt

• Odor: Slight

Application: Rubber Parts Demolding

• Diluent: Water

• Feature: Environmental Friendly

Advantages: Water Based

• Highlight: Belts Water Based Release Agent,

Hihg Performance Water Based Release Agent

Product Description

Environmental Friendly Water Based Elevator Handrail Mold Release Agent Lubricant

It is a milky water based release agent, which can be widely used in traditional drive belt, cutting belt, cutting belt, etc. It can be used with high dilution, the surface of the tape products is dry, wireless marks, no missing materials, and high cost performance, which can effectively meet the needs of customers for high-performance products and cost-effective release agents. At present, the release agent products circulating on the market, the dilution ratio is low, and the release performance of the rubber material requirements are higher, in the terminal application often form the same production tape manufacturers to match the use of multiple grades of release agent products, in order to meet the release needs.

Elevator Handrail release agent Advantages:

High dilution: dilution can be diluted with tap water, high environmental protection and low cost.

Easy to use: suitable for spraying, brushing, wiping, dipping, etc.

Suitable for a wide temperature range, grinding tools can be used directly at room temperature and high temperature.

Release Agent Application:

Molds should be clean before using.

Apply a thin coat of our release agent.

Wait until the water is evaporated.

Start production

Handling precautions:

For industrial use only.

Prolonged skin contact with high concentrate dilutions should be avoided. Accidental splashes in the eye should be washed out with copious amounts of water.

Do not allow product to freeze.

Other applications

Application	Suitable code	Dispersing medium	Advantages
Antivibration	Lubekote 9421A/ 9140	Water based	Environmentally friendly; Can be diluted multiple times; It has strong durability and good releasing effect; Excellent performance of surface gloss; Costeffective; Prolongs the mold cleaning cycle.
Seals & Gaskets	Lubekote 9165C	Water based	Can be used as both semi-permanent and highly diluted. Applied as semi- permanent it has strong durability and good releasing effect; Excellent performance of surface gloss; Cost- effective;
Hose	Lubekote 9240	Water based	Environmentally friendly; Excellent anti- tack agent for rollers, drums and autoclave vulcanisation operations
Belt	Lubekote 9836A	Water based	Environmentally friendly; Good releasing effect.
Tire	Lubekote 9919	Water based	Semi-permanent lubricant system designed for coating of Bladders and touch up coats on Bladders or Green Tires; Easy to apply; Provides true multiple releases; Universal for all tires.
Tire	Lubekote 9502A/9503A	Water based	Semi-permanent water-based release agent applied on tire molds. The gloss level of part surface gloss is adjustable.
Silicone & Fluorine rubber	Lubekote 9165C	Water based	Applied for releasing hard-to-release rubber such as fluorine rubber; Can be used as both semi-permanent and highly diluted. As semi-permanent it has strong durability and good releasing effect; Excellent performance of surface gloss; Cost-effective; Good performance on post process;
Silicone & Fluorine rubber	Lubekote 9440A	Water based	Applied to release silicone and EPDM; Designed for molding operations when non-transfer of release agent, high temperature stability, high degree of slip, and abrasion resistance of the release film are important.
CPU	Lubekote 9120A	Water based	Environmentally friendly; Easy to apply; Prolongs the mold cleaning cycle.

Flexible foam	Lubekote 9820A	Water based	Environmentally friendly; Low VOC; Delicate skin, highly diluted; Less contaminating mold.
ISF	Lubekote 9810G	Water based	5~10 times dilution; Cost-effective; Less contaminating mold; strong demolding; Universal for all ISF.
Encapsulatio n	Lubekote 9808E	Water based	Matt finish; Excellent performance of produced parts; Less contaminating mold; strong demolding; Universal for all encapsulation.

Common Issues:

The surface is oily and shiny.

The rubber powder is difficult to remove

serious lines

Our release agent can well solve these kinds of problems.







Shanghai Lorechem Co., Ltd. was established in 2008. It is a high-tech enterprise which is dedicated to serve releasing products which involve semi-permanent release agent, anti-sticking, surface lubrication and thermal reactive adhesive.







shlorechem.com

Floor 2-3, Building 20, Hongxing International Plaza, Lane 1818, Lianhang Road, Pujiang, Shanghai