

Insoluble In Water Molded Rubber Release Agent Liquid Status And **Solubility**

Basic Information

• Place of Origin: China • Brand Name: Lubekote Model Number: 9165C/9330C

• Minimum Order Quantity:

None

• Price: negotiation · Packaging Details: 20L, 200L

• Delivery Time: 10-15 working days

• Payment Terms: T/T

• Supply Ability: 20T/month



Product Specification

• Feature: **Environmental Friendly** • Instructions: External Release Agent

· Color: Clear/white

• Application: Rubber Seal Parts

• Compatibility: Works With Most Rubber Materials • Safety Precautions: Wear Protective Gloves And Eyewear

· Status: Liquid · Shelf Life: 1 Year

• Highlight: Water Molded Rubber Release Agent,

> Molded Rubber Release Agent, Liquid Molded Rubber Release Agent

Insoluble In Water Molded Rubber Release Agent Liquid Status and Solubility

Product Description:

The main function of Lubekote rubber release agent is to prevent rubber products from sticking to the surface of the mold, and to make rubber products smoothly out of the mold without tearing.

It is a flexible water-based rubber mold release agent engineered to deliver exceptional longevity, prolonged release efficacy, and no transfer characteristics for all rubber and elastomeric compounds.







Features:

Product Name: Rubber Mold Release Agent

Instructions: External Release Agent Solubility: Insoluble In Water Application: Rubber Molded Parts

Status: Liquid

Safety Precautions: Wear Protective Gloves And Eyewear

Cost-effective Strong release power

Easy to use

Applications:

The mold must be cleaned meticulously.

Ensure thorough stirring of the release agent before application.

The product is prepared for immediate use. For a smoother release, consider diluting it by adding 1-3 parts of water, preferably deionized. Apply a fine layer of Lubekote release agent. Commence production once the water has evaporated.

Support and Services:

The Rubber Mold Release Agent is a specialized product designed to assist in the release of rubber molds from their respective molds. Our Technical Support team is available to provide guidance on the best application techniques for your specific mold and release agent combination. Additionally, we offer a range of services to ensure that our product is meeting your needs, including laboratory testing, product customization, and on-site support. Contact us for more information on how we can help you achieve optimal results with our Rubber Mold Release Agent.

More release agent for Rubber Industry:

Application	Suitable code	Dispersing medium	Advantages
Antivibration	Lubekote 9421A/ 9140	Water based	Environmentally friendly; Can be diluted multiple times; It has strong durability and good releasing effect; Excellent performance of surface gloss; Cost-effective; Prolongs the mold cleaning cycle.
Antivibration	Lubekote 9526	Solvent based	It has strong durability and good releasing effect; Excellent performance of surface gloss; Economical dosage; Prolongs the mold cleaning cycle.Excellent performance of surface gloss; Cost-effective; Good performance on post process; Prolongs the mold cleaning cycle applied as both semi-permanent and highly diluted.

			It has strong durability and good releasing effect;
Antivibration	Lubekote 9425	Solvent based	Less build-up on molds; Cost-effective; Good
			performance on post process.
			Environmentally friendly; Excellent anti-tack agent
Hose	Lubekote 9240		for rollers, drums and autoclave vulcanisation
			operations
Hose	Lubekote 9808		Non greasy, non contaminating coating; Good
			releasing effect; Excellent performance of
			produced parts.
Belt	Lubekote 9836A	Water based	Environmentally friendly; Good releasing effect.
Belt	Lubekote 9328	Solvent based	Fast drying; Good releasing effect; Cost-effective.
Tire	Lubekote 9919	Water based	Semi-permanent lubricant system designed for
			coating of Bladders and touch up coats on
			Bladders or Green Tires; Easy to apply; Provides
			true multiple releases; Universal for all tires.
			Semi-permanent water-based release agent
Tire	Lubekote 9502A/9503A	Water based	applied on tire molds. The gloss level of part
			surface gloss is adjustable.
Silicone & Fluorine rubber	Lubekote 9165C	Water based	Applied for releasing hard-to-release rubber such
			as fluorine rubber; Can be used as both semi-
			permanent and highly diluted. As semi-permanent
			it has strong durability and good releasing effect;
			Excellent performance of surface gloss; Cost-
			effective; Good performance on post process;

Shanghai Lorechem Co., Ltd. was established in 2008. It is a high-tech enterprise which is dedicated to serve releasing products which involve semi-permanent release agent, anti-sticking, surface lubrication and thermal reactive adhesive.









shlorechem.com

Floor 2-3, Building 20, Hongxing International Plaza, Lane 1818, Lianhang Road, Pujiang, Shanghai