

Water Based Mold Release Agent For Rubber Molding EPDM / FKM / ACE

Our Product Introduction

for more products please visit us on shlorechem.com

Basic Information

- Place of Origin: China
- Brand Name: Lubekote
- Certification: ISO 9001
- Model Number: 9165C/9330C
- Minimum Order Quantity: None
- Price: negotiation
- Packaging Details: 20L, 200L
- Delivery Time: 10-15 working days
- Payment Terms: T/T
- Supply Ability: 20T/month



Product Specification


- Compatibility: Works With Most Rubber Materials
- Diluent: Deionized Water, Distilled Water
- Color: Clear/white
- Feature: Environmental Friendly
- Safety Precautions: Wear Protective Gloves And Eyewear
- Instructions: External Release Agent
- Shelf Life: 1 Year
- Status: Liquid
- Highlight: **EPDM Rubber Mold Release Agent, Water Based Rubber Mold Release Agent, FKM Rubber Mold Release Agent**

Water Based Mold Release Agent for Rubber Molding EPDM/FKM/ACE

Product Description:

Our Rubber Mold Release Agent is a powerful solution that provides a strong release power, which helps in the easy extraction of finished parts from the mold. Our release agent is semi-permanent, which means that it can be used several times, reducing the need to reapply the release agent frequently, making it a cost-effective solution.

Our Rubber Mold Release Agent is specifically designed for the production of rubber molded parts. It is formulated to work with most rubber materials, making it easy to use in most production processes. Our release agent works by creating a barrier between the mold and the rubber material, reducing the risk of damage to the finished product, and increasing the lifespan of the mold.





Features:

Product Name: Rubber Mold Release Agent

Shelf Life: 1 Year

Solubility: Insoluble In Water

Diluent: Deionized Water, Distilled Water

Instructions: External Release Agent

Color: Clear/white

Cost-effective

Water based release agent

Applications:

Make sure to meticulously clean the mold, removing any residues or contaminants that could affect the casting process.

Before applying the release agent, thoroughly stir it to ensure uniform consistency and optimal performance.

The release agent is prepared for immediate use. If a smoother release is desired, you can dilute it by adding 1-3 parts of water. For the best results, use deionized water to maintain the quality of the mixture.

Apply a fine, even layer of Lubekote release agent to the mold surface. Allow the water from the mixture to evaporate completely before commencing the production process to ensure proper adhesion and effectiveness of the release agent.

Support and Services:

The Rubber Mold Release Agent product technical support and services include:

- Assistance with product selection and application
- Troubleshooting and problem-solving for product-related issues
- Recommendations for proper usage and handling
- Safety information and guidance for handling the product
- Regulatory compliance information
- Technical documentation and product data sheets

More release agent for Rubber Industry:

Application	Suitable code	Dispersing medium	Advantages
Antivibration	Lubekote 9421A/ 9140	Water based	Environmentally friendly; Can be diluted multiple times; It has strong durability and good releasing effect; Excellent performance of surface gloss; Cost-effective; Prolongs the mold cleaning cycle.
Antivibration	Lubekote 9526	Solvent based	It has strong durability and good releasing effect; Excellent performance of surface gloss; Economical dosage; Prolongs the mold cleaning cycle. Excellent performance of surface gloss; Cost-effective; Good performance on post process; Prolongs the mold cleaning cycle applied as both semi-permanent and highly diluted.

Antivibration	Lubekote 9425	Solvent based	It has strong durability and good releasing effect; Less build-up on molds; Cost-effective; Good performance on post process.
Hose	Lubekote 9240	Water based	Environmentally friendly; Excellent anti-tack agent for rollers, drums and autoclave vulcanisation operations
Hose	Lubekote 9808	Solvent based	Non greasy, non contaminating coating; Good releasing effect; Excellent performance of produced parts.
Belt	Lubekote 9836A	Water based	Environmentally friendly; Good releasing effect.
Belt	Lubekote 9328	Solvent based	Fast drying; Good releasing effect; Cost-effective.
Tire	Lubekote 9919	Water based	Semi-permanent lubricant system designed for coating of Bladders and touch up coats on Bladders or Green Tires; Easy to apply; Provides true multiple releases; Universal for all tires.
Tire	Lubekote 9502A/9503A	Water based	Semi-permanent water-based release agent applied on tire molds. The gloss level of part surface gloss is adjustable.
Silicone & Fluorine rubber	Lubekote 9165C	Water based	Applied for releasing hard-to-release rubber such as fluorine rubber ; Can be used as both semi-permanent and highly diluted. As semi-permanent it has strong durability and good releasing effect; Excellent performance of surface gloss; Cost-effective; Good performance on post process;

Shanghai Lorechem Co., Ltd. was established in 2008. It is a high-tech enterprise which is dedicated to serve releasing products which involve semi-permanent release agent, anti-sticking, surface lubrication and thermal reactive adhesive.



Shanghai Lorechem Company Limited



15901891635



export@lorechem.com



shlorechem.com

Floor 2-3, Building 20, Hongxing International Plaza, Lane 1818, Lianhang Road, Pujiang, Shanghai