

Liquid Status Environmentally Rubber Mold Release Agent Silicone-free Lubricant

Our Product Introduction

for more products please visit us on shlorechem.com

Basic Information

- Place of Origin: China
- Brand Name: Lubekote
- Certification: ISO
- Model Number: 9165C/9330C
- Minimum Order Quantity: None
- Price: negotiation
- Packaging Details: 20L, 200L
- Delivery Time: 10-15 working days
- Payment Terms: T/T
- Supply Ability: 20T/week



Product Specification


- Feature: Environmental Friendly
- Diluent: Deionized Water, Distilled Water
- Safety Precautions: Wear Protective Gloves And Eyewear
- Compatibility: Works With Most Rubber Materials
- Solubility: Insoluble In Water
- Shelf Life: 1 Year
- Instructions: External Release Agent
- Application: Rubber Molded Parts
- Highlight: **Environmentally Rubber Mold Release Agent ,
Silicone-free Rubber Mold Release Agent ,
Liquid Status Rubber Mold Release Agent**

Environmentally Rubber Mold Release Agent Silicone-free Lubricant

Product Description:

Our Rubber Mold Release Agent is designed to make your job easier. With its strong release power, you can be confident that your molds will release easily and cleanly, without sticking or tearing. And because it is water-based, it is easy to dilute with deionized water or distilled water to achieve the desired consistency for your project.

Our release agent produces a durable film on the mold surface capable of providing many releases before reapplication is necessary. It will not contaminate the released surface. It is water-based. It is ready to use. But it can be diluted in some cases.





Features:

Product Name: Rubber Mold Release Agent

Shelf Life: 1 Year

Status: Liquid

Instructions: External Release Agent

Diluent: Deionized Water, Distilled Water

Features:

Semi-permanent release agent

Strong durability

Excellent release properties

Reduces defects and increases efficiency

Improves mold life and reduces maintenance costs

Applications:

Ensure thorough cleaning of the mold.

Properly stir the release agent prior to application.

The product is prepped for immediate use. To ensure a smooth release, consider diluting it with 1-3 parts of water, preferably deionized.

Apply a light layer of Lubekote release agent. Begin production after the water has evaporated.

Support and Services:

Our Rubber Mold Release Agent is a high-quality product designed to provide superior performance in the release of rubber components from molds without causing any damage to the mold or the component. Our technical support team is available to provide guidance on the optimal usage of the product to ensure the best results. In addition, we offer a range of services including product training, troubleshooting, and on-site application support to help our customers get the most out of our Rubber Mold Release Agent.

More release agent for Rubber Industry:

Application	Suitable code	Dispersing medium	Advantages
Antivibration	Lubekote 9421A/ 9140	Water based	Environmentally friendly; Can be diluted multiple times; It has strong durability and good releasing effect; Excellent performance of surface gloss; Cost-effective; Prolongs the mold cleaning cycle.
Antivibration	Lubekote 9526	Solvent based	It has strong durability and good releasing effect; Excellent performance of surface gloss; Economical dosage; Prolongs the mold cleaning cycle. Excellent performance of surface gloss; Cost-effective; Good performance on post process; Prolongs the mold cleaning cycle applied as both semi-permanent and highly diluted.

Antivibration	Lubekote 9425	Solvent based	It has strong durability and good releasing effect; Less build-up on molds; Cost-effective; Good performance on post process.
Hose	Lubekote 9240	Water based	Environmentally friendly; Excellent anti-tack agent for rollers, drums and autoclave vulcanisation operations
Hose	Lubekote 9808	Solvent based	Non greasy, non contaminating coating; Good releasing effect; Excellent performance of produced parts.
Belt	Lubekote 9836A	Water based	Environmentally friendly; Good releasing effect.
Belt	Lubekote 9328	Solvent based	Fast drying; Good releasing effect; Cost-effective.
Tire	Lubekote 9919	Water based	Semi-permanent lubricant system designed for coating of Bladders and touch up coats on Bladders or Green Tires; Easy to apply; Provides true multiple releases; Universal for all tires.
Tire	Lubekote 9502A/9503A	Water based	Semi-permanent water-based release agent applied on tire molds. The gloss level of part surface gloss is adjustable.
Silicone & Fluorine rubber	Lubekote 9165C	Water based	Applied for releasing hard-to-release rubber such as fluorine rubber ; Can be used as both semi-permanent and highly diluted. As semi-permanent it has strong durability and good releasing effect; Excellent performance of surface gloss; Cost-effective; Good performance on post process;



Shanghai Lorechem Company Limited



export@lorechem.com



shlorechem.com

Floor 2-3, Building 20, Hongxing International Plaza, Lane 1818, Lianhang Road, Pujiang, Shanghai