

Semi-Permanent Rubber Mold Release Agent Silicone Fluorine Rubber Multiple Release Demolding

Our Product Introduction

for more products please visit us on shlorechem.com

Basic Information

- Place of Origin: China
- Brand Name: Lubekote
- Certification: ISO 9001
- Model Number: Lubekote 9165C
- Minimum Order Quantity: 25L
- Price: 1-99 USD
- Packaging Details: 25L, 200L
- Delivery Time: 5-15 working days
- Payment Terms: T/T
- Supply Ability: 20T/week



Product Specification

- Product Name: Rubber Mold Release Agent
- Classification: Chemical
- Odor: Slight
- Application: Demolding For Silicone And Fluorine Rubber
- Advantage: Semi-permanent Multiple Releases
- Highlight: **semi-permanent rubber mold release, silicone fluorine rubber release agent, multiple release demolding agent**



More Images



Product Description

Lubekote 9165C is a semi-permanent rubber mold release agent formulated for hard-to-release silicone and fluorine rubber. It delivers strong durability and a good releasing effect while producing excellent surface gloss on molded parts. The product can be used either as a semi-permanent coating or highly diluted for economical application, giving manufacturers flexibility across different production requirements. Its cost-effective performance and good post-process characteristics make it a preferred choice for demanding silicone and fluoroelastomer molding where conventional release agents struggle.

Key Features

- **Semi-Permanent Release:** Provides multiple releases from a single application for lower labor costs.
- **Hard-To-Release Rubber:** Effectively releases silicone and fluorine rubber compounds.
- **Strong Durability:** Maintains a durable release film across extended production runs.
- **Excellent Surface Gloss:** Produces molded parts with a premium, glossy finish.
- **Flexible Dilution:** Usable as semi-permanent coating or highly diluted for economy.
- **Good Post-Process Performance:** Supports clean bonding and finishing after demolding.

Technical Specifications

Parameter	Specification
Product Name	Rubber Mold Release Agent
Brand Name	Lubekote
Model Number	Lubekote 9165C
Classification	Chemical release agent
Diluent	Water
Odor	Slight
Application	Demolding for silicone and fluorine rubber
Feature	Environmentally friendly

Applications

Lubekote 9165C is engineered for silicone rubber and fluorine rubber molding, including O-rings, gaskets, seals, and precision elastomer components. It is compatible with steel and aluminum molds and applies by spray or brush. The semi-permanent film is especially effective on complex geometries and high-temperature silicone and fluoroelastomer molding, where reliable release and fine detail reproduction are essential to part quality and productivity.

Packaging & Quality Assurance

Lubekote 9165C is packed in 25L and 200L containers and delivered within 5-15 working days. Each batch is quality-checked for durability, release performance, and surface gloss. Store in a cool, dry place away from freezing temperatures. This product is for industrial use only; avoid prolonged skin contact and rinse eyes with water immediately on contact.



Shanghai Lorechem Company Limited



15901891635



export@lorechem.com



shlorechem.com

Floor 2-3, Building 20, Hongxing International Plaza, Lane 1818, Lianhang Road, Pujiang, Shanghai